Press open, plug in and close again.

Either way, the cover is closed whether the unit is in use or not.

Because the cover shields and protects. Because it looks good. Because it can be in the colour of your choice. And because it means that you can push any excess cable through the slot and stow it underneath.

3-7
MODULES

MOST POPULAR CONFIGURATIONS

133 º0 € • 2P1USBC2













RECOMMENDED FOR: Conference and

meeting rooms





For available communications and power modules see pages 78 and 79

BENEFITS

simply press lightly to open, plug in and close

••

socket position makes it easy to plug in

..

sockets are always protected from dust and liquids

••

available in all colours

PLASTIC **ELEMENTS** COVER

Black

Brushed stainless steel

White stainless

MODULES

stee

Black

Black stainless

ALUMINIUM

Black

Any RAL colour on request

stee

VOLTAGE 100-250 V max

CURRENT

16 A max

FREQUENCY 50-60 Hz

TEMPERATURE 0 – 40°C

RELATIVE HUMIDITY 0 – 95 % (non-condensing)

PROTECTION IP 42







INSTALLATION

Fits into a rectangular opening. Dimensions given in instructions

Mounts on desk of thickness between 12 to 60 mm

CABLES

Standard

Integrated 20 cm cable with EPN3MO connector

On request

any length and connector