

# DALI-Gateway S128 KNX

Item no.: 4940302



Home and Building control  
KNX

## Description

- Interface between the DALI and the KNX system, DALI-2 certified
- 2 channels for 2x64 DALI lights
- A maximum of 64 DALI members can be connected to a DALI output
- Control of DALI devices in 16 groups or in individual control (from firmware 0.3.x and ETS application V2)
- Support of DALI "Device Type 8" (DT8) for controlling light color, brightness and color temperature
- Time-dependent color control (also for Human Centric Lighting applications)
- Scene module for up to 16 different groups
- Effect module for sequencers
- Energy saving by switching off the ECG voltage supply in the groups (communication object)
- Simple replacement of ECGs in the event of a fault
- The DALI start-up takes place via the ETS plug-in



## Technical data

DALI-Gateway S128 KNX	
Operating voltage KNX	Bus voltage, <10 mA
Operating voltage	100 – 240 V AC/DC 50 – 60 Hz
Frequency	50 – 60 Hz
Width	4 modules
Installation type	DIN rail

DALI-Gateway S128 KNX	
Type of connection	Terminal screws   Bus connection: KNX bus terminal
Ambient temperature	-5°C ... 45°C
Stock temperature	-25°C ... 70°C
Protection class	I
Type of protection	IP 20

Subject to technical changes and misprints

additional information at: [www.theben.de/product/4940302](http://www.theben.de/product/4940302)

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.