

Listwy zasilające CONFERENCE i TOP FRAME

#										
---	--	--	--	--	--	--	--	--	--	--

X-Large | Wejście/wyjście zasilające: GST18i3 | Szerokość 444 mm

909.009	6					35°				2
909.008	5					35°				3
909.007	4					35°				4
909.0057	3					35°			•	4
909.006	3					35°				5
909.005	2					35°				6
909.0026		4				45°				2
909.0058		3				45°			•	2
909.0027		3				45°				3
909.0029		2				45°				5
909.0028		2				45°				4
909.016			6			35°				2
909.015			5			35°				3
909.014			4			35°				4
909.0060			3			35°			•	4
909.013			3			35°				5
909.012			2			35°				6
909.020*				6		0°				3
909.0191				4		0°				4
909.0172				3		0°			•	4
909.033*				2		0°				6
909.0080					5	35°				3
909.0105					3	35°			•	4

X-Large | Bez wejścia/wyjścia zasilającego | Szerokość 444 mm

909.001						0°				8
---------	--	--	--	--	--	----	--	--	--	---



909.009



909.008



909.007



909.0057



909.006



909.005



909.001



Materiał: profil z anodowanego aluminium
Kolor gniazda: czarny

Odpowiednie przewody zasilające – zob. od str. 54.



Odpowiednie moduły indywidualne – zob. od str. 146.