


EMUF 20 LG

Locknut flame-retardant, polyamide, RAL 7035, M20



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Polyamide UL94-V0
Temp. range min	-40 °C
Temp. range max	100 °C
Glow wire test	960 °C
Hazard level EN acc. 45545	R22=HL3 / R23=HL3 / R24=HL3
Thread type	M
Ø Connection thread D	20
Lead	1,5
Total length TL	5 mm
Key width SW	27 mm
Collar diameter (E)	29 mm
Product Color	RAL 7035
Order no. RAL 7035	10060812
Type	EMUF 20 LG
Packing unit	100
EAN number	4007685608121
Tariff number	39269097
ETIM-Classification	EC000940

09.09.2024


Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com